Large Format Print Solutions ideal for Poster, Display Graphics and In-house Print.

iPF6300S

you can

iPF63005 24 INCH 2,400 X 1,200 DPI 8 COLOURS GLOSSY A1 IN 2 MINUTES 49.6 SQM/HR 160GB HDD 30,720 NOZZLES BORDERLESS PRINTING ECONOMY PRINTING MODE

Key features

- New LUCIA EX pigment ink system and improved image processing technology delivering:
 - Wider colour gamut
 - Smoother gradation, deeper dark tones and sharper blacks
 - Improved scratch resistance and reduced bronzing
 - Higher print registration accuracy for precise text and fine lines
- High speed, economical printing with new Fast mode





- Built in 160GB Hard Disk Drive enabling storage of large print jobs which are easily accessible direct from the printers LCD panel
- Borderless printing, so no need for offline trimming saving time and money
- Manage print costs and track ROI full accounting and job costing software included
- Economy mode for lower running costs - reduces ink consumption
- Large, bright and easy to use LCD operation panel easy access to sophisticated functions
- Choice of printer driver settings tailored to suit expertise of user

- User friendly simple roll paper loading and control the print from the front
- Bundled with free of charge PosterArtist Lite poster creation software – makes it easy to produce professional looking posters
- Print plug-ins for MS Office, Photoshop and Digital Photo Professional:
 - 64 bit compatibility
 - Photoshop plug-in has been enhanced to include CMYK (as well as RGB)
- Gigabit Ethernet compatible enabling fast data transfer, even for data-heavy files or high volume print jobs

📣 imagePROGRAF



Specifications: iPF6300S

Model Class Ink Type Maximum Print Resolution Installation	PF6300S 24-inch Pigment ink ; LUCIA EX ;8-color pigment ink: BK, MBK, C, M, Y, PC, PM, GY 2400 x 1200dpi User installation	
PRINTING SPEEDS (A1 ROLL)		
Plain Paper	0:35 (Fast Economy)	
Coated Paper	1:56 (Standard) 1:02 (Fast Economy)	
Photo Glossy Paper	1:56 (Standard) 2:08 (Fast Economy) 3:08 (Standard)	
PRINTER STAND		
Type Installation conditions	Optional, Assembly type User installation	
DIMENSIONS, WEIGHT (Net) W x D x H (mm), (kg)		
Main unit with Auto Roll Feed Unit (standard) Main unit and Printer Stand	1,177 (W) x 670 (D) x 344 (H) mm; Weight: approx. 51kg (excluding consumables and Printer Stand) 1,177 (W) x 870 (D) x 991 (H) mm; Weight: approx. 66kg (excluding consumables)	М
DIMENSIONS, WEIGHT (Packaged) W x D x H (mm), (kg)		
Main unit (pallet included) Printer Stand	1,320 (W) x 914 (D) x 645 (H) mm; Weight: approx. 79 kg 1,115 x 864 x 237 mm, Weight: approx. 22 kg	MA
POWER		
Input power Power consumption Power Save Mode 100 V - 120V 220 V - 240 V Power off (standby) Operational Environment	AC 100 - 240 V 50 - 60 Hz) Operation: 100 W or less 6 W or less 7 W or less 1 W or less 1 Emperature: 15 - 30°C, Humidity: 10 - 80 %	
ACOUSTIC NOISE	·	
Acoustic pressure Acoustic power	Operation: 47dB (A), Standby: 35 dB (A) or less Operation: approx 6.4Bels,	
MEMORY		
Standard memory	384 MB	
PRINTER LANGUAGES		
Printer language	GARO (Graphic Arts language with Raster Operations)	EN
OPERATION PANEL		
Display Displayable Language on LCD	Large LCD US-English, French, German, Italian, Spanish, Russian,	
INTERFACE		Roll H
Hi-Speed USB Ethernet Standard Protocol	Built-in Built-in 10base-T, 100base-TX, 1000base-T IPX/SPX, SNMP HTTP, TCP/IP (IPv4/IPv6), AppleTalk	
PRINT HEAD		
Model Type Head configuration Nozzle pitch Droplet size	PF-05 Bubble-jet on demand 6 colours integrated type (2 print head) 1, 200 dpi x 2 4 pl	Some This I Final trade
INK TANK		Cano to se
Model Colours Capacity	PFI-105: BK, MBK, C, M, Y, PC, PM, GY BK, MBK, C, M, Y, PC, PM, GY Starter use: 90 ml, Sales use: 130 ml	

CUTTER Туре Automatic horizontal cutting Rotary cutter, independent unit MEDIA HANDLING Roll paper Manual feed (1 sheet) One Roll (top-loading [front operation possible], front output) Front loading and front output, top loading and front output Plain and coated paper, technical paper, film, photographic paper, Media types proofing paper, backlit, self adhesive, banner and sign, fine art printing material MEDIA SIZE Media Core size Internal diameter of roll core: 2" / 3" MEDIA THICKNESS Roll paper Manual feed from the top Manual feed from the front 0.07 - 0.8 mm 0.07 - 0.8 mm 0.5 - 1.5 mm MEDIA WIDTH Roll paper 203.2 mm - 610 mm 203.2 mm - 610 mm Roll paper Manual feed from the top Manual feed from the front 250 - 610 mm (24"); POP board use only: A2, A1 1INIMUM PRINTABLE LENGTH Roll paper Manual feed from the top Manual feed from the front 203.2 mm 279.4 mm 350 mm AXIMUM PRINTABLE LENGTH Roll paper 18 m (Varies according to the OS and application) Manual feed from the top 1.6 m Manual feed from the front 914 mm BORDERLESS PRINTING (ROLL MEDIA ONLY) 10" (254 mm), B4 (257 mm), A3+ (329 mm), 14" (356 mm), 16" (407 mm), A2 (420 mm), A2+/17" (432 mm), B2 (515 Media width mm), A1 (594 mm), 24" (610 mm) MEDIA FEED CAPACITY Manual feed 1 sheet (from top, from front) REGULATIONS Electrical safety regulations Europe Germany Russia CE mark TUV Gost-R (locally obtained) Other countries CB certification VIRONMENT CERTIFICATIONS ENERGY STAR WW, RoHS directive, IT ECO Declaration Europe, WEEE, ErP Lot 6 (Europe) OPTION Printer stand Holder Set (3-inch core spindle) ST-25 RH2-25 (2-inch core roll holder with 3-inch paper tube attachment and borderless print spacer) CONSUMABLES PFI-105: BK, MBK, C, M, Y, PC, PM, GY Ink Tank Print Head PF-05 Maintenance Cartridge MC-16 ne images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. I leaflet and the specifications of the product have been developed prior to the date of product launch. al specifications are subject to change without notice.^m and ©: All company and/or product names are lemarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. ion recommends you use Canon Media for the best results. Please check media (paper) compatibility list ee which variety of paper/media is recommended.



Canon Inc. canon.com

English Edition © Canon Europa N.V., 2011

Canon Europe

canon-europe.com

Full-photolithography Inkjet Nozzle Engineering

Canon (UK) Ltd Woodhatch Reigate, Surrey RH2 8BF

Tel: 01737 220000 Fax: 01737 220022 www.canon.co.uk



Canon Ireland Arena Road, Sandyford Industrial Estate Dublin 18, Ireland

Tel: 01 2052400 Fax: 01 2958141 www.canon.ie

