

# Small yet highly productive

imageRUNNER  
1133, 1133A and 1133iF

**you can**

This compact multifunctional series features double-sided document output as standard and optional Wi-Fi. Time and cost saving capabilities ensure you hit deadlines and save money too.

UP TO <b>33</b> PPM / CPM, A4 BLACK-AND-WHITE
UP TO <b>1,050</b> SHEET CAPACITY
NETWORK READY, PCL*, AND OPTIONAL PS AND WI-FI
<b>5-LINE</b> USER INTERFACE
CLASS-LEADING ENERGY EFFICIENCY
EMBEDDED UNIFLOW AND E-MAINTENANCE CAPABILITY



The image shown above is the imageRUNNER 1133



The image shown above is the imageRUNNER 1133iF

## Productivity and efficiency.

- Fast print speeds up to 33ppm
- Up to 1050 sheet paper capacity
- 50 sheet Duplex Document feeder\*
- Print and scan directly from USB memory key and Send in Colour to email and network folder\*
- Simple, hassle-free integration - Network ready, optional WiFi, PCL and PS support\*
- Compatibility with Canon's e-Maintenance service offers remote diagnostics, automated meter readings and consumables monitoring

\* Available on selected models- please see specifications for full details

## Environmental.

- Energy Star certified and low TEC rating
- Consumes as little as 2.5 watts in sleep mode
- Save paper - automatic double-sided output

## Cost Control.

- Compatibility with uniFLOW solution offers Cost Centre selection and reporting for cost control and monitoring
- Accurate billing through e-Maintenance
- Enhanced productivity and class-leading energy efficiency maximises value

## Security .

- Secure Print\*\* keeps documents confidential during printing
- Department ID secures access to the device
- Canon's uniFLOW solution offers the flexibility and convenience of My Print Anywhere secure release

\*\* RAM-based secure print for up to 5 jobs

imageRUNNER

**Canon**

# Specifications: imageRUNNER 1100 series

<b>imageRUNNER 1133 series</b>	
Machine Type	Mono Laser Multifunctional.
Available Core functions	imageRUNNER 1133: Print, Copy, Scan imageRUNNER 1133A: Print, Copy, Scan imageRUNNER 1133IF: Print, Copy, Scan, Send and Fax
<b>PRINTER SPECIFICATIONS</b>	
Print speed	Up to 33 ppm (A4)
Printing method	Monochrome laser beam printing
Print Resolution	600 x 600 dpi, Up to 1200 x 1200 dpi (Enhanced)
Double sided printing	Automatic
Printing from memory media	Supported memory media: USB memory key
Paper input (Standard)	Supported file types: JPEG, TIFF 500-sheet paper cassette 50-sheet multi-purpose tray
Paper input (Option)	500-sheet cassette
Maximum paper input capacity	1050 sheets
Paper output capacity	50-sheets (60-89gsm)
Finishing capabilities	Group
Supported media types	Cassette and optional cassette: Plain paper, Recycled paper, Heavy paper, Bond Multi-purpose tray: Plain paper, Recycled paper, Heavy paper, Bond, Transparency, Label, Envelope
Supported media sizes	Cassette and optional cassette: A4, A5, B5, Legal, Letter, Executive Multi-purpose tray: A4, A5, B5, Legal, Letter, Executive, Statements, Envelope (COM10, Monarch, DL, ISO-CS, ISO-B5) Custom sizes: Width: 76 to 216 mm; Length: 127 to 356 mm 60 to 128 g/m <sup>2</sup>
Supported media weights	Cassette and optional cassette: 60 to 190 g/m <sup>2</sup>
Printer Language(s)	Stack Bypass: UFR II-LT(Standard) PCL5e/6 (Standard with iR1133IF, Option on iR1133/A) PostScript Level 3 Emulation (Option for all models)
Fonts	PCL fonts: 93 Roman PS fonts: 136 Roman UFR II-LT: Windows® 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later)
Operating system compatibility	Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7/ Server 2008 R2, MAC OS X (10.4.9 or later) PPD: MAC OS 9.1 or later, MAC OS X (10.2.8 or later) Windows 2000/ Server 2003/ Server 2008/ XP/ Vista/ 7 Please refer to <a href="http://software.canon-europe.com">http://software.canon-europe.com</a> for availability of print solutions for other Operating Systems and environments including AS/400, UNIX, Linux and Citrix. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place
<b>COPY SPECIFICATIONS</b>	
Copy speed	Up to 33 cpm (A4)
First Copy Output Time (FCOT)	Approx. 8 seconds or less
Copy resolution	Up to 600 x 600 dpi
Multiple copy	Up to 99 copies
Reduction / Enlargement	25-400% in 1% increments
Other features	4 on 1, ID Card Copy
<b>SCAN SPECIFICATIONS</b>	
Optional/Standard	Standard

Type	imageRUNNER 1133: Colour Flatbed imageRUNNER 1133A: Colour Flatbed and Duplex Automatic Document Feeder (DADF) imageRUNNER 1133IF: Colour Flatbed and Duplex Automatic Document Feeder (DADF)
Supported media size/s	A4, A5, Legal, Letter, Custom sizes (W x L): Max 215.9 mm x 355.6 mm Min. 139.7 mm x 128 mm)
Supported media weight/s	Single-sided scanning: 50 to 105 g/m <sup>2</sup> Double-sided scanning: 64 to 105 g/m <sup>2</sup>
Scan resolution	Pull Scan Platen: up to 600 dpi in Black and White or Colour DADF: up to 300 dpi in Black and White or Colour 2-sided to 2-sided (Automatic)
Double sided scanning	One-sided Scan BW 600 dpi: 14 ipm(A4) Scan BW 300 dpi: 28 ipm(A4) Scan CLR 300 dpi: 9 ipm(A4) Scan BW 600 dpi: 7 ipm(A4) Scan BW 300 dpi: 10 ipm(A4) Scan CLR 300 dpi: 6 ipm(A4)
Scan speed	Two-sided Scan BW 600 dpi: 14 ipm(A4) Scan BW 300 dpi: 28 ipm(A4) Scan CLR 300 dpi: 9 ipm(A4) Scan BW 600 dpi: 7 ipm(A4) Scan BW 300 dpi: 10 ipm(A4) Scan CLR 300 dpi: 6 ipm(A4)
Scan methods	Push Scan: Send functionality available on iR1133IF only. Pull Scan: TWIN Pull scanning available on all models Yes on all models Scan to USB Memory Key: TWIN Via MF Toolbox Windows 2000/ Windows XP/ Windows Server 2003/ Windows Vista/ Windows Server 2008/ Windows 7
Pull scan specifications	
<b>SEND SPECIFICATIONS</b>	
Optional/Standard	Standard on iR1133IF. Not supported on iR1133/A models
Send resolution	Platen/DADF: up to 300 dpi in Black and White or Colour E-Mail/ PC(SMB, FTP) Max. 200
Destinations	Address Book / Speed dials
File formats	TIFF (B&W), JPEG, PDF, PDF (Compact)
Universal Send	No
Feature Sets	
<b>FAX SPECIFICATIONS</b>	
Optional/Standard	Standard on iR1133IF. Not supported on iR1133/A models
Modem Speed	Super G3 33.6kbps (Up to 3 seconds/page <sup>1</sup> )
Fax Resolution	Standard: 200 x 100 dpi Fine: 200 x 200 dpi Photo: 200 x 200 dpi Super fine: 200 x 400 dpi Ultra fine: 400 x 400 dpi
Fax Memory	Up to 512 pages <sup>1</sup>
Speed Dials	Max. 200 (including, 19 one-touch dials)
Group Dials/ Destinations	Max. 199 dials/ Max.199 destinations
Sequential Broadcast	Max. 201 locations
Memory backup	1 hour
Other features	Fax Forwarding, Dual Access, Remote Reception, PC Fax (TX only)
<b>GENERAL SPECIFICATIONS</b>	
Warm-up Time	Approx. 11 seconds or less from power on
Interface type	USB 2.0 Hi-Speed 10BASE-T/100BASE-TX Optional Wireless 802.11b/g 1 x Host USB interface (Front of device) Optional additional Host USB interface for uniFLOW MiCARD reader (Right-side of device)
Network protocols	TCP/IP (LPO/ Port 9100, HTTP), SMB, SNMP v1, WSD, IPv4/ IPv6 support
Processor Speed	300 Mhz
Memory	256 MB (shared)
Hard Disk Drive	No (RAM-based Secure Print standard)

Control panel	5-line monochrome backlit LCD display
Dimensions with trays (W x D x H)	iR1133 (platen model): 450 x 472 x 413mm / 450 x 472 x 550mm (with optional cassette) iR1133A/IF (ADF models): 450 x 472 x 465mm / 450x472x603mm (with optional cassette) iR1133A/IF: 450 x 1,141 x 724 mm (with the optional paper cassette attached) iR1133: 450 x 1,044 x 721 mm (with the optional paper cassette attached) iR1133IF: Approx. 20.7 kg (21.5 kg with Starter Cartridge) iR1133A: Approx. 20.5 kg (21.3 kg with Starter Cartridge) iR1133: Approx. 18.3 kg (19.1 kg with Starter Cartridge)
Installation space (W x D x H)	
Weight	
Power Source	220-240 V (±10%), 50/60 Hz (±2 Hz)
Power Consumption	Maximum: Approx. 1200 W Standby: Approx. 9 W Sleep Mode: Approx. 2.5 W Typical Electricity Consumption (TEC): 1.3 kWh on all models
Noise Levels	Sound Pressure <sup>2</sup> Active: 70.6 dB or less Standby: 43 dB or less
Software and printer management	iWMC - Centralised management of the device eMaintenance compatibility - enables Meter reading, Automatic consumables management and remote diagnostics NetSpot Device Installer MF Toolbox Remote User Interface (RUI) Department ID Management uniFLOW Login Device Client - Embedded uniFLOW Compatibility
Security Features	IP/ Mac Address Filtering, Department ID, Secure Print (RAM-based), Simple Job Release via uniFLOW (Option)
<b>CONSUMABLES</b>	
Toner Cartridge/s	C-EXV40 TONER (6,000 pages <sup>3</sup> ) Ships with Starter Cartridge (2,200 pages <sup>3</sup> )
<b>SPECIFICATIONS FOR OPTIONS</b>	
Cassette Feeding Unit	Name: Canon Cassette Feeding Module-Z1 Dimensions: 450 x 472 x 138 mm Weight: Approx. 5.2 kg
<b>ADDITIONAL OPTIONS</b>	
Additional Options	PS Printer Kit-AP1 PCL Printer Kit-AP1 Wireless Network Option-C1 Barcode Printing Kit-E1: Provides Barcode printing capability using Jet Caps technology MiCARD Attachment Kit-A1: For uniFLOW MiCARD reader, add one USB I/F on right-side of device Canon Copy Card Reader-F1: Physical card access system that limits access to authorised users Card Reader Attachment Kit-G1: Attachment kit for Card Reader-F1 Copy Control Interface Kit-C1: For coin vending solutions Canon Cassette Feeding Module-Z1: Additional 500-sheet cassette Plain Pedestal: The pedestal can be placed under the standard/optional cassette feeding unit to raise the device when free-standing
<b>FOOTNOTES</b>	
[1] Based on ITU-T Standard Chart No. 1	
[2] Declared noise emission in accordance with ISO 7779	
[3] Based on 6% coverage	
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice.™ and ® All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.	
Microsoft, Windows and Windows Vista is either a registered trademark or trademark of Microsoft Corporation in the United States and/or other countries.	



Canon Inc.  
canon.com

Canon Europe  
canon-europe.com

11/10/V1  
UK English edition 0157W184  
© Canon Europa N.V., 2011

Canon (UK) Ltd  
Woodhatch  
Reigate  
Surrey RH2 8BF  
Telephone no 01737 220000  
Facsimile 01737 220022  
canon.co.uk

Canon Ireland  
3006 Lake Drive  
Citywest, Saggart  
Co.Dublin, Ireland  
Telephone No: 01 2052400  
Facsimile No: 01 2052525  
canon.ie

