

imageRUNNER 2520/i, 2525/i, 2530/i, 2535/i, 2545/i

Compact workgroup
productivity

you can

Be more productive and reduce costs with the compact imageRUNNER 2500 series. Ideal for busy, small and medium workgroups, this versatile range provides for everyday black-and-white printing, copying, colour scanning and advanced send direct to email and network folder. With a variety of speeds up to 45ppm, excellent responsiveness and energy efficiency these devices will save you time, money and energy.

A range of speeds from 20 to
45ppm / cpm, A3 black-and-white

Up to 2,300 sheet paper capacity

Send direct to email and network folder

5.7inch / 14.47cm touch screen display

Class-leading energy efficiency

Compact design



Productivity and efficiency.

- Easy-to-use touch-screen display saves time and enables users to do more
- Fast everyday black-and-white printing up to 45ppm to meet the demands of busy, small-to-medium-sized workgroups
- Highly responsive – rapid recovery from sleep mode and 3.9 seconds first copy out time*
- Send in colour to a network folder or email in a variety of formats**. Save time by automatic resolution of email addresses
- Fewer interruptions with up to 2,300 sheet paper capacity
- Scan directly to USB memory key**

Compact design.

- Space-saving design to fit busy offices
- Optional inner staple and collate finisher

Environmental.

- Exceptional energy efficiency – as little as 1.5 watts power consumption in sleep mode, saves energy and cost
- Save paper – automatic double-sided output

Cost-effective.

- Low cost of ownership
- Enhanced productivity and class-leading energy efficiency maximises value
- Department ID Management helps monitor and control printing costs

Connectivity and management.

- Network interface with Remote User Interface as standard
- PCL** and optional PostScript Level 3 emulation support
- Remotely manage and monitor with iW Management Console (iWMC)
- Compatible with Canon's e-Maintenance tool – remote diagnostics, automated meter readings and consumables monitoring capability

* imageRUNNER 2535/i, 2545/i models

** Standard on i models, optional on non i models

imageRUNNER

Canon

Specifications: imageRUNNER 2500 Series

Type Maximum Original Size Copy Sizes	Cassette 1, 3, 4 A3 A3, A4, A4R, A5R Custom size: 139.7 to 297mm x 182 to 432mm	Desktop or Free-standing (Reader-Printer Combined)
Resolution	Cassette 2 Stack Bypass Custom Size Reading Copying Printing Number of Tones	A3, A4, A4R, A5R A3, A4, A4R, A5R 99 to 297mm x 148 to 432mm 600dpi x 600dpi 600dpi x 600dpi 600dpi x 600dpi, 1200dpi x 1200dpi (UFRII-LT only) 256 Gradations
COPY/PRINT SPEED	A4 A3 Magnification First Copy Time Warm-Up Time Multiple Copies/Prints Duplexing	imageRUNNER 2545i / 2545: 4.5ppm (BW) imageRUNNER 2535i / 2535: 3.5ppm (BW) imageRUNNER 2530i / 2530: 3.0ppm (BW) imageRUNNER 2525i / 2525: 2.5ppm (BW) imageRUNNER 2520i / 2520: 2.0ppm (BW) imageRUNNER 2545i / 2545: 2.2ppm (BW) imageRUNNER 2535i / 2535: 2.2ppm (BW) imageRUNNER 2530i / 2530: 1.5ppm (BW) imageRUNNER 2525i / 2525: 1.5ppm (BW) imageRUNNER 2520i / 2520: 1.5ppm (BW) 25-400%; Fixed: 25%, 50%, 70%, 100%, 141%, 200%, 400% 3.9 sec (4.5 / 35ppm model), 5.4 sec (30 / 25ppm model), 6.4 sec (20ppm model) 30 seconds 1 to 999 sheets Standard
Paper Weight	Cassette	64 to 90g/m ² ; Stack Bypass: 64 to 128g/m ² ; Duplex: 64 to 80g/m ² ;
Paper Capacity	Cassette 1 Cassette 2 Stack Bypass Optional Total Capacity	550 sheets (80g/m ²), (250 sheets for the imageRUNNER 2520i / 2520) 550 sheets for imageRUNNER 2525i/i, 2530i/i, 2535i/i, 2545i/i 50 envelopes 100 sheets (A4, A4R, A5; 80g/m ²), 50 sheets (A3; 80g/m ²) 550 sheets x 2 cassettes (80g/m ²) 550 sheets x 1 cassette for imageRUNNER 2520 / 2520i only 2,300 sheets, (2,000 sheets for the imageRUNNER 2520i / 2520) Canon Custom Processor, 400MHz 512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models) Ethernet (100Base-TX / 10Base-T), USB Host1 / F 2.0 x 1 port, USB Device 1.0 x 1 port 220-240V AC, 50/60Hz, 4.2A (4.5 / 35ppm model), 220-240V AC, 50/60Hz, 3.3A (3.5 / 30 / 20ppm model) 1.827kW (4.5 / 35ppm model), 1.345kW (30 / 25ppm), 1.542kW (20ppm model) imageRUNNER 2545i / 2545 / 2535i / 2535 - 565 x 680 x 806mm (with the platen cover), 565 x 689 x 907mm (with the DADF) imageRUNNER 2530i / 2530 / 2525i / 2525 - 565 x 680 x 806mm (with the platen cover), 565 x 689 x 896mm (with the DADF) imageRUNNER 2520i / 2520 - 565 x 680 x 681mm (with the platen cover), 565 x 689 x 771mm (with the DADF) imageRUNNER 2545i / 2535i: Approx. 78.4kg, imageRUNNER 2545 / 2535: Approx. 70.5kg imageRUNNER 2530i / 2525i: Approx. 77.5kg, imageRUNNER 2530 / 2525: Approx. 68.0kg imageRUNNER 2520i: Approx. 56.0kg, imageRUNNER 2520: Approx. 50.5kg
Max. Power Consumption	Interface	
Dimensions (W x D x H)	Power Supply	
Weight		
PRINT SPECIFICATION		
PDL		UFRII-LT, PCL5e/6 (standard on i models, optional on non i models), PostScript level 3 emulation (optional)
Resolution		600 x 600dpi, 1200dpi x 1200dpi (UFRII-LT only)
Memory		512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models)
CPU		Canon Custom Processor, 400MHz
Fonts		PS Fonts: Roman 136, PCL Fonts: Roman 93
Supported OS		PCL: Windows 2000 / XP / Server2003 / Vista / Server2008 / Windows 7 Postscript level 3 emulation: Windows 2000 / XP / Server2003 / Vista / Server2008 / Windows 7, Mac OS X (10.4 or later) UFRII-LT: Windows 2000 / XP / Server2003 / Vista / Server2008 / Windows 7, Mac OS X (10.4 or later), Linux Mac-PPD: Mac OS X 10.4 or later Ethernet (100Base-TX / 10Base-T) TCP / IP (LPD / Port9100, HTTP), SMB, SNMPv1, WSD, IPv4 / IPv6 support Network TWAIN Driver (75 / 100 / 150 / 200 / 300dpi 8bit colour / 75-600dpi 1bit Black-and-White)
SEND SPECIFICATION/ CLR SEND KIT-Y1 (standard on i models, optional on non i models)		
Scan Speed (A4, 300dpi, BW/Colour)		45 / 34ipm (4.5 / 35ppm model), 25 / 13ipm (3.0 / 2.5 / 20ppm model)
Scan Resolution	BW	100 x 100dpi, 150 x 150dpi, 200 x 100dpi, 200 x 200dpi, 200 x 400dpi, 300 x 300dpi, 400 x 400dpi, 600 x 600dpi
Destinations	CL	100 x 100dpi, 150 x 150dpi, 200 x 200dpi, 300 x 300dpi E-Mail / Internet FAX (SMTP), PC / Server (SMB, FTP), IWDM USB memory keys Local (Max. 500)
Address Book File Format		TIFF, JPEG, PDF, High compression PDF, Searchable PDF (optional with Searchable PDF-C1)

DADF-AA1 for imageRUNNER 2545/2535	Paper Size Paper Weight	A3, A4, A4R, A5, A5R Single sided original: 42 to 128g/m ² , Double sided original: 50 to 128g/m ² 100 sheets (A4, A4R, A5, A5R: 80g/m ²), 50 sheets (A3: 80g/m ²)
Max. Number of Originals Document Scanning Speed (max.)	Copy Scan	4.5ipm (A4, 600 x 600dpi: BW) 4.5 / 34ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour) 565 x 540 x 137mm Approx. 7.9kg
Dimensions (W x D x H) Weight		
DADF-AB1 for imageRUNNER 2530/2525/2520	Paper Size Paper Weight	A3, A4, A4R, A5, A5R Single sided original: 37 to 128g/m ² , Double sided original: 50 to 128g/m ² 50 sheets (A4, A4R, A5, A5R: 80g/m ²), 25 sheets (A3: 80g/m ²)
Max. Number of Originals Document Scanning Speed (max.)	Copy Scan	2.5ipm (A4, 600 x 600dpi: BW) 2.5 / 13ipm (A4, 600 x 600dpi: BW / 300 x 300dpi: Colour) 565 x 544 x 126mm Approx. 7.0kg
Dimensions (W x D x H) Weight		
CASSETTE UNIT-W1 for imageRUNNER 2520/i	Type Paper Size Custom Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight	Front-loading adjustable drawers A3, A4, A4R, A5R 139.7 to 297mm x 182 to 432mm 64 to 90g/m ² 550 sheets (80g/m ²) x 1 cassette 565 x 680 x 97mm Approx. 12.8kg
CST. FEEDING UNIT-AE1 for all models	Type Paper Size Custom Size Paper Weight Paper Capacity Dimensions (W x D x H) Weight	2 Front-loading adjustable drawers A3, A4, A4R, A5R 139.7 to 297mm x 182 to 432mm 64 to 90g/m ² 550 sheets (80g/m ²) x 2 cassettes 565 x 680 x 248mm Approx. 24.0kg
INNER FINISHER-B1 for all models	Number of Trays Tray Capacity Staple Position Staple Capacity Dimensions (W x D x H) Weight	One stack tray (Optional 2nd Tray: Inner Fin. Add. Tray-B1) A4, A5, A5R: 1,000 sheets (or 125mm in height) A3, A4R: 500 sheets (or 62.5mm in height) Corner, Double A4: 50 sheets x 30 sets; A4R / A3: 30 sheets x 15 sets 416 x 554 x 350mm, 703 x 554 x 350mm (with output tray extended) Approx. 12.5kg
INNER 2-WAY TRAY-G1 for all models	Number of Trays Tray Capacity Dimensions (W x D x H) Weight	2 stack tray A4: 250 sheets, A3: 100 sheets A4: 100 sheets, A3: 50 sheets 426 x 413 x 109mm Approx. 0.6kg
OTHER ACCESSORIES		Platen Cover Type P: for imageRUNNER 2525/2530 without DADF Platen Cover Type O: for imageRUNNER 2535/2545 without DADF Stamp Ink Cartridge-C1 Stamp Unit-B ADF Access Handle-A1 PCL Printer Kit-AF1: Supports PCL5e and PCL6 printing for non-i Models PS Printer Kit-AF1: Supports PostScript Level 3 Emulation printing Barcode Printing Kit-B1: Provides Barcode printing capability using Jet Caps technology Super G3 Fax Board-AG1: Add fax functionality FL Cassette-A11: This spare 550-sheet tray for cassette '1' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i FL Cassette-AK1: This spare 550-sheet tray for cassette '2' of imageRUNNER 2525 / 2525i / 2530 / 3530i / 2535 / 2535i / 2545 / 2545i or for Cassette Feeding Unit-AE1 or Cassette Module-W1 FL Cassette-AL1: This spare 250-sheet tray for cassette '1' of imageRUNNER 2520 / 2520i allows you to swap paper sizes without changing the printer settings Cassette Spacer-A1: Adjusts the height for 250-sheet cassette when combined with optional Cassette Feeding Unit-AE1 or Cassette Module-W1 on imageRUNNER 2520 / 2520i only imageRUNNER 2500 Plain Pedestal 2-Way Unit-B1: Enhances the double-sided print productivity up to 100% Reversal Pass Unit (2-Way Unit) option for imageRUNNER 2520 / 2520i / 2525 / 2530 Staple-J1: Staples for Inner Finisher-B1 Document Tray-J1: Handy tray that attaches to the side of the device Power Supply Unit-U1 Card Reader Attachment-D3: Attachment kit for Card Reader-E Canon Card Reader-E1: Physical card access system that limits system access to authorised users USB Application 3-Port Interface Kit-A1: 3-Port USB interface kit for USB memory CCV1 / F Cable-A1: Interface Kit for Coin-Vender C-EXV33 TONER BK: Toner for imageRUNNER 2520 / 2520i / 2525 / 2525i / 2530 / 2530i C-EXV32 TONER BK: Toner for imageRUNNER 2535 / 2535i / 2545 / 2545i



Canon Inc.
www.canon.com

Canon Europa
www.canon-europe.com

English-UK Edition
© Canon Europa 2010 (0210)

Canon (UK) Ltd
Woodhatch, Reigate
Surrey RH2 8BF
Telephone No: 01737 220000
Facsimile No: 01737 220022
www.canon.co.uk

Canon Ireland
Arena Road, Sandyford
Industrial Estate
Dublin 18, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2958141
www.canon.ie